



CANADA GOLD SINGLE GRADE DIESEL ENGINE OILS are optimal for use in naturally aspirated, turbo charged or super charged diesel engines in passenger, pick up and delivery vehicles as well as in construction, farm and marine equipment requiring a single grade diesel engine oil. This formulation provides excellent varnish, sludge, carbon and oxidation control and protects against bearing and bushing corrosion.

SAE GRADE	50W
Density @ 15°C, Kg/L	0.8973
Kinematic Viscosity (D445):	
cSt @ 40°C	208
cSt @ 100°C	20.4
Viscosity Index (D2270)	136
Flash Point (D92), °C	210
Pour Point (D97), °C	-18
CCS Viscosity, cP @ -20°C	0.0
Sulphated Ash, mass%	1.00%
TBN	9
Foam Test	Pass
*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES	

Applications: Meets or exceeds the following service requirements:

- Exceeds API service classification CF, CF-2, GF-3
- Recommended for Power Shift Transmissions specifying:
- Allison C-3, C-4
- Cat TO-2
- Recommended for mobile hydraulic equipment systems specifying engine oil