



**CANADA GOLD GASOLINE ENGINE OILS** are formulated for turbo charged and naturally aspirated gasoline, natural gas and propane engines in passenger vehicles and light duty service trucks. It lubricates, cools and protects turbo charged and high revving engines that operate at high temperatures. The formulation helps protect engines by controlling varnish, deposits, rust, corrosion, wear and cleanliness.

SAE GRADE	5W20	5W30	10W30
Density (D4052) kg/m@ 15°C	863	863	872
Kinematic Viscosity (D445):			
cSt @ 40°C	49.7	58.9	69.5
cSt @ 100°C	8.6	10.6	10.6
Viscosity Index (D2270)	150	155	140
CCS Viscosity (D2602):	341	341	
cP @ -30°C	6100	6300	~
cP @ -25°C	~	~	6300
Flash Point (D92), °C	218	224	234
Pour Point (D97), °C	-42	-42	-36
Colour (ASTM)	3.0	3.0	3.0
Ash Sulphate, mass%	0.92%	0.92%	0.92%
*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES			

Applications: Meets or exceeds the following service requirements:

- Gasoline engines for passenger vehicles and trucks that specify API service SN, SM, SL, SJ, SH, SG, SF requirements.
- Propane engines for passenger vehicles and trucks
- Natural gas engines
- Upholds the warranty requirements for passenger vehicles and light duty trucks that specify ILSAC starburst GF-1, GF-2, GF-3, GF-4 and GF-5 engines